

Ø100 Differential Bottom Connection Manometers

Used for pressure measurement of liquids and gases.

Usage Sectors:

- Machinery manufacturing industry
- Iron and Steel Industry
- Chemical and Petro-chemical industry
- Ship Industry
- Food and beverage industry
- Power Plant
- Heavy industrial applications and so on



Model No: **S10012**

Product Specifications

STANDARD FEATURES			
Accuracy Class:	1,6		
Mechanism:	Brass or Stainless Steel 316 L		
Case:	Brass or Stainless Steel		
Frame:	Brass or Stainless Steel		
Connection:	Brass or Stainless Steel 1/4 BSP (Other size threads on the request)		
Pressure Unit:	Brass or Stainless Steel Bourdon Tube		
Dial:	Aluminum, black division on white base or white division on black base		
Scale Unit:	bar/psi		
Scale Range:	0-1 bar /psi	0-16 bar /psi	0-160 bar /psi
	0-2,5 bar /psi	0-25 bar /psi	0-250 bar /psi
	0-4 bar /psi	0-40 bar /psi	0-315 bar /psi
	0-6 bar /psi	0-60 bar /psi	0-600 bar /psi
	0-10 bar /psi	0-100 bar /psi	0-1000 bar /psi

TECHNICAL DETAILS	
Standard:	EN 837-1
Environment Temperature:	-20...+60°C
Warehouse Temperature:	-40...+70°C
Madde İsişi:	Special production is required if used up to 60 ° C for soft solder, up to 100 ° C for hard solder, up to 200 ° C at higher temperatures.