

Ø100 Standard Back Connection with U Clamp Manometers

- Used for pressure measurement of liquids and gases.



Model No: **A 1003**

Product Specifications

STANDARD FEATURES				
Accuracy Class:	1,6			
Mechanism:	Brass			
Case:	Steel, chrome or black oven painted			
Frame:	Steel, black oven painted, chrome or acrylic			
Connection:	Brass 1/2 BSP (Other size threads on the request)			
Pressure Unit:	Cu Sn 8 Bourdon Tube			
Dial:	Aluminum, black division on white base or white division on black base			
Scale Unit:	bar/psi			
Scale Range:	-1 - 0 bar /psi	0-1 bar /psi	0-16 bar /psi	0-160 bar /psi
	-760..0 Hgmm	0-2,5 bar /psi	0-25 bar /psi	0-250 bar /psi
	-1- +3 bar /psi	0-4 bar /psi	0-40 bar /psi	0-315 bar /psi
	-1-+5 bar /psi	0-6 bar /psi	0-60 bar /psi	0-600 bar /psi
	-1-+15 bar /psi	0-10 bar /psi	0-100 bar /psi	0-1000 bar /psi

TECHNICAL DETAILS	
Standard:	EN 837-1
Environment Temperature:	-20...+60°C
Warehouse Temperature:	-40...+70°C
Madde İsisı:	Special production is required if used up to 60 ° C for soft solder, up to 100 ° C for hard solder, up to 200 ° C at higher temperatures.

FEATURES ON THE REQUEST	
<ul style="list-style-type: none"> ½ NPT or other size thread Special dial printing Stainless Steel Connection and Bourdon Tube Stainless and chrome case or frame 	