

Ø100 1 CL Glycerine Filled Bottom Connection Manometers

- Used for pressure measurement of liquids and gases.



Model No: **FA10015**

Product Specifications

| STANDARD FEATURES | | | | |
|-------------------|--|----------------|----------------|-----------------|
| Accuracy Class: | 1,0 | | | |
| Mechanism: | Brass | | | |
| Case: | Steel, chrome or black oven painted | | | |
| Frame: | Stainless Steel | | | |
| Connection: | Brass 1/2 BSP (Other size threads on the request) | | | |
| Pressure Unit: | CuSn8 Bourdon Tube | | | |
| Dial: | Aluminum, black division on white base or white division on black base | | | |
| Scale Unit: | bar/psi | | | |
| Filling Liquid: | Glycerine | | | |
| Scale Range: | -1 - 0 bar /psi | 0-1 bar /psi | 0-16 bar /psi | 0-160 bar /psi |
| | -760..0 Hgmm | 0-2,5 bar /psi | 0-25 bar /psi | 0-250 bar /psi |
| | -1- +3 bar /psi | 0-4 bar /psi | 0-40 bar /psi | 0-315 bar /psi |
| | -1-+5 bar /psi | 0-6 bar /psi | 0-60 bar /psi | 0-600 bar /psi |
| | -1-+15 bar /psi | 0-10 bar /psi | 0-100 bar /psi | 0-1000 bar /psi |

| TECHNICAL DETAILS | |
|--------------------------|---|
| Standard: | EN 837-1 |
| Environment Temperature: | -20...+60°C |
| Warehouse Temperature: | -40...+70°C |
| Madde İsişi: | Special production is required if used up to 60 ° C for soft solder, up to 100 ° C for hard solder, up to 200 ° C at higher temperatures. |

| FEATURES ON THE REQUEST | |
|-------------------------|-------------------------|
| ▪ | ½ NPT other size thread |
| ▪ | Special dial printing |